

HRLITE T8 LED-Röhren AC Single- / Doppelend 140lm/W

- PF>95%
- Aluminiumlegierung + PC-Abdeckung
- SVM<0.4, PstLM \leq 1
- LED-Chip 2835
- Zertifikat: CE, RoHs
- Not dimmable
- 30.000 Std. / 15.000 Schaltzyklen



Model Nr.	Artikel-Nr.	Volts	End Cap	CRI	CCT (K)	Lumen per watt	Watt	Energy efficiency	Beam Angle	Colour consistency in McAdam ellipses
SWEI T8 28x43.8cm LED Tube	SWEI-T81F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	7	C	160	6SDCM
SWEI T8 28x60cm LED Tube	SWEI-T82F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	11	C	160	6SDCM
SWEI T8 28x90cm LED Tube	SWEI-T83F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	15	C	160	6SDCM
SWEI T8 28x105cm LED Tube	SWEI-T83.5F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	18	C	160	6SDCM
SWEI T8 4F 28x140cm LED Tube	SWEI-T84F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	22	C	160	6SDCM
SWEI T8 28x150cmmm LED Tube	SWEI-T85F-XXK-AL	100-277V	G13	82	2000-6500K	120~150	25	C	160	6SDCM